



## Note

### Note

#### SERRAFILO AUTOMATICO DEGLI ART. 1673/... - 1675/... - ET..

##### Sezione dei cavetti per i serrafilo in entrata

Solidi:	0,5-2,5 mm <sup>2</sup> (1673/...)
	0,5-2,5 mm <sup>2</sup> (1675/..., ET..)
Cordati:	0,5-2,5 mm <sup>2</sup> (1673/...)
	0,75-2,5 mm <sup>2</sup> (1675/..., ET..)
Flessibili:	1,5-2,5 mm <sup>2</sup>

##### Sezione dei cavetti per i serrafilo in uscita

Solidi:	(a) 0,5-1,5 mm <sup>2</sup>
	(b) 0,5-2,5 mm <sup>2</sup>
	(c) 0,5-0,75 mm <sup>2</sup>

##### Spelatura

- con sezioni 0,5-1 mm<sup>2</sup>: 8-9 mm
- con sezioni 1,5-2,5 mm<sup>2</sup>: 9-10 mm
- con sezioni 0,5-0,75 mm<sup>2</sup>: 9-11 mm (1673/...)

#### PUSH WIRE TERMINALS OF ART. 1673/... - 1675/...- ET...

##### Section of wires for input side terminals

Solid:	0,5-2,5 mm <sup>2</sup> (1673/...)
	0,5-2,5 mm <sup>2</sup> (1675/..., ET..)
Stranded:	0,5-2,5 mm <sup>2</sup> (1673/...)
	0,75-2,5 mm <sup>2</sup> (1675/..., ET..)
Flexible:	1,5-2,5 mm <sup>2</sup>



##### Section of wires for output side terminals

Solid:	(a) 0,5-1,5 mm <sup>2</sup>
	(b) 0,5-2,5 mm <sup>2</sup>
	(c) 0,5-0,75 mm <sup>2</sup>

##### Stripping

- cable with 0,5-1 mm<sup>2</sup> sections: 8-9 mm
- cable with 1,5-2,5 mm<sup>2</sup> sections: 9-10 mm
- cable with 0,5-0,75 mm<sup>2</sup> sections: 9-11 mm (1673/...)

**SERRAFILO IN ENTRATA**  
**INPUT SIDE TERMINALS**



**SERRAFILO IN USCITA**  
**OUTPUT SIDE TERMINALS**